

DIRECTIONAL WARNING LIGHT LED - built in

SPECIFICATIONS

- Voltage: 12-24V

- Nominal power: 12W (4x LED)

- Flash patterns: 21 patterns (amber or blue)

- Housing: aluminium

L-shaped bracket included

- Ingress protection (IP rating): IP67, IP69K

- Approvals: ECE R65 / ECE R10

- Operating temperature: from -40°C to +60°C

 Installation: round rubber sealing ring L-shaped bracket included























ELEX59084-B

Sturdy aluminum housing and L-shaped bracket included









ELEX59244-B

Positive VDC "+"	 red
Negative / ground "-"	 black
Flash pattern and SYNC (1)	 yellow
Low intensity (2)	white

(1) To change the flashing pattern, apply the **yellow** wire to the **black** wire. Less than 1s for the next pattern, 3 to 5s for the previous pattern, and 6 to 9s to return to pattern 1.
(2) To reduce the intensity, apply the **white** wire to the **black** wire.

PART NO.	COLOR	OPTIONAL COLOR	VOLTAGE	POWER / LEDs	INSTALLATION	APPROVAL	IP
ELEX59084-B			12-24V	12W / 4x LED	rubber seal ring L-shaped bracket included	ECE R65	IP67
ELEX59244-B						EMC R10	IP69K